

Quotation: E-19016

Reference: PR-191014

CAST RESIN TRANSFORMER

1250 kVA

Losses Family		AoAk-Reg548	Installation		indoor
Vector group		Dyn11	Type of cooling		AN
Frequency	Hz	50	Installation altitude	m.s.l	<1000
Phases		3	Total harmonic distorsion	THDv	<5%

	HV Winding	LV1 Winding	LV2 Winding
Nominal rated power at cont. Service	1250kVA	1250kVA	
Nominal voltage (at no load)	33kV	400V	
Off-load tapping links	+2 / -3 x 4,545 %		
Connection	Delta	Star	
Insulation class [kV]	36	≤ 1,1	
AC [kv]	70	3	
BIL [kV]	170	-	
Winding material	Al	Al	
Type of winding	Cast in mould under vacuum	Impregnated under vacuum	

INSULATION AND TEMPERATURE CLASS

Max Ambient temperature °C

40

	HV Winding	LV1 Winding	LV2 Winding
Insulation temperature class	°C	155°C (F)	155°C (F)
Temperature rise of windings	K	100	100
Environmental, Climatic, Fire classes	E2-C2-F1		(Type Test Certificate CESI A9032391)

GUARANTEED VALUES AT VOLTAGE RATIO OF:

33000 / 400 V

(Tolerances according to the mentioned Standards)

1250 kVA

	W		Tolerance, Po	%	
No-load loss, Po	W	2070	Tolerance, Po	%	0%
No-load current, Io	%	1	Tolerance, Io	%	30%
Load loss, °C	W	12100	Tolerance, °C	%	0%
Impedance voltage, Uk	%	6	Tolerance, Uk	%	±10%
Partial discharge value	pC				<10
Sound level Power, Lwa	dB(A)				67

OVERALL DIMENSIONS AND WEIGHTS (Preliminary)

Length x Width x Height (IP00)	mm	2050	1310	2310	CRT Mass [kg]	4700
Length x Width x Height (IP31)	mm				Box Mass [kg]	
Rollers distance	mm	1070 x 1070				

PAINTING (subject to availability)

Magnetic core	RAL	9005	Box	RAL	
Frames	RAL	9005			

According to EU 548/2014

ACCESSORIES AND TESTS

In the price quoted, is included a set of routine tests at our test room according to IEC 60076-11 standard. For each transformer, a specific Test Report will be issued

Code Nr.	Description	Qty	Unit price CRT
-	HV terminals	3	Included in the price
-	LV bus bar terminals	4	Included in the price
-	Off load tapping links	3	Included in the price
-	Rating plate	1	Included in the price
-	Lifting lugs	4	Included in the price
-	Earth terminals	2	Included in the price
-	Orientable rollers	4	Included in the price
200074	3 Pt100 probes wired to terminal box IP65 >=2500	1	Included in the price
220023	MT200 LITE CONTROL UNIT	1	Included in the price
CB01414	+40% kVA. Temporary Increase ventilation bars 50Hz	1	Included in the price
220035	VRT-200 CONTROL UNIT	4	Included in the price

Notes

Antiseismic frame (Horizontal Peak Ground Acc): <=0.2g (light earthquakes)

Headquarters
Via Triumplina, 179
25136 Brescia (BS) - Italy
Tel. +39 030 2017.100
Fax +39 030 2009.726
www.legrand.com

Faxes
administr. dpt. +39 0302003712
domestic sales: +39 0302009726
export sales: +39 0302007159
purchasing dpt.: +39 0302005650

Head Office
Bticino SpA
viale Luigi Borri, 231
21100 Varese - Italy

M 7.01.06 Rev 2 ENG
Page 6
Capitale sociale euro 98.800.000 i.v
R.I. Milano e C.F. 10991860155
P.IVA IT10991860155
S.p.A. a socio unico
Gruppo Legrand